CP-30W ANALOG COLOR PRINTER

MITSUBISHI ELECTRIC
INDUSTRIAL IMAGING

High Resolution, High Speed Industrial Printer With Easy And Reliable Operation.

KEY FEATURES

- 423 dpi high resolution printing
- New adaptive thermal head management control engine for vivid, smear-free gradation
- Ultra-fast print speeds
- Automatic loading for trouble-free ribbon cartridge replacement
- Easy to use, convenient front loading design
- Paper cassette engineered for easy mounting
- Space saving unit storage
- Effective heat and dust case design
- Built-in lighting to track print status
- Wide-mouth paper catcher
- Long lasting quality and reliability

SPECIFICATIONS	
Printing System	Dye sublimation thermal transfer
Head Resolution	423 dpi
Print Resolution (Dots)	1600 x 1200 (S-size); 2100 x 1600 (L-size)
Gradation	256 gradation each for YMC; 16.7 million hue full color
Paper Size	S-size 3.94 x 3.70" (100 x 94 mm); L-size 3.94 x 5.83" (100 x 148 mm)
Print Size	S-size 3.78 x 2.99" (96 x 76 mm); L-size 3.78 x 5.00" (100 x 127 mm)
Paper Capacity	S-size 80 sheets; L-size 50 sheets
Print Speed	S-size <16 sec.; L-size <25 sec.
Interface	RGB analog, S video, composite video
Memory Capacity	8-frame memory
Contol Terminal	RS-232C (D-Sub 25 pin) rear mounted remote port (Mini DIN 8 pin, stereo mini-jack)
Dimensions (W x H x D)	8.35 x 4.92 x 16.73" (212 x 125 x 425 mm)
Weight	16.1 lbs. (7.3 kg) main unit only
Power Supply	120V AC 50/60 Hz; 220-240V AC 50/60 Hz
Power Current Consumption	120V AC 50/60 Hz: 1.7A (printing), 0.3A (standby) 220-240V AC 50/60 Hz: 1.0A (printing), 0.3A (standby)
Regulatory Approvals	EN60950-1, EN60601-1, TUV-GS, TUV-GM UL60950-1, UL6060-1 CSA C22.2 No. 60950-1, No. 60601.1
Accessories	AC power cord, paper cassette, instruction manual, CD-ROM Windows© XP/2000 compatible

NOTES: Print speed and power consumption are valued for "standard" printing mode.
The printer is not a medical device, thus, any printed images are for reference only and it should not be used for diagnosis unless such application has been designed under approval as diagnostic imaging equipment. The MAC OSX printer driver (up to version 10.4) may be downloaded from the Mitsubishi Electronics printer website at www.mitsubishi-imaging.com/industrial.

OPTIONS (Paper/Ink Ribbon Sets)	
CK30S	S-size printing paper and ribbon cartridge, 80 sheets x 3 packs
CK30L	L-size printing paper and ribbon cartridge, 50 sheets x 4 packs
CK30S4P*	S-size overcoat printing paper and ribbon cartridge, 60 sheets x 3 packs
CK30L4P*	L-size overcoat printing paper and ribbon cartridge, 40 sheets x 4 packs

** Option will be available soon.*

©2009 Mitsubishi Digital Electronics America, Inc.
Standard features, options and specifications subject to change without notice. All trademarks or registered trademarks are the property of their respective holders.

Mitsubishi Digital Electronics America, Inc.
Imaging Products Division
9351 Jeronimo Road, Irvine, CA 92618
Toll Free: 888-307-0388
ipdinfo@mdea.com

www.mitsubishi-imaging.com/industrial

Technical Support:
Toll Free: 888-307-0309
Email: tsupport@mdea.com

Canada:
Mitsubishi Electric Sales Canada Inc.
Information Technologies Group
Markham, Ontario
905-475-7728

www.MitsubishiElectric.ca

IP9049-11/09-WEB